



We recommend genuine Spicer®

A Outside Diameter	B Wall Thickness	S - Seamless W - Welded D.O.M - Drawn Over Mandrel	Tube Inside Diameter	C		
				TUBING PART NUMBER		
				54/68" Length	73/74" Length	100" Length
1.250"	.095"	W - D.O.M.	1.057"	--	--	10-30-42-10000
1.250"	.120"	S	1.010"	--	--	10-32-92-10000
1.250"	.188"	W - D.O.M.	.876"	--	--	10-32-72-10000
1.750"	.065"	W	1.620"	14-30-12-5400	--	14-30-12-10000
1.750"	.095"	W	1.560"	--	14-30-62-7400	14-30-62-10000
2.000"	.065"	W	1.870"	--	--	16-30-32-10000
2.000"	.083"	W	1.834"	16-30-62-5400	16-30-62-7400	16-30-62-10000
2.000"	.083"	W - D.O.M.	1.834"	--	--	DT16-30-62
2.000"	.120"	W	1.760"	--	--	16-30-102-10000
2.000"	.120"	W - D.O.M.	1.760"	--	--	DT16-30-102
2.500"	.065"	W	2.370"	20-30-12-5400	20-30-12-7400	20-30-12-10000
2.500"	.083"	W	2.334"	--	20-30-22-7400	20-30-22-10000
2.500"	.083"	W - D.O.M.	2.334"	--	--	DT20-30-22
2.500"	.095"	W	2.310"	20-30-52-5400	--	20-30-52-10000
2.750"	.065"	W	2.620"	--	22-30-12-7400	22-30-12-10000
2.750"	.065"	W - D.O.M.	2.620"	--	--	DT22-30-12
2.750"	.083"	W	2.584"	--	--	22-30-22-10000
3.000"	.065"	W	2.870"	--	24-30-32-7400	24-30-32-10000
3.000"	.065"	W - D.O.M.	2.870"	--	--	DT24-30-32
3.000"	.083"	W	2.834"	--	24-30-42-7400	24-30-42-10000
3.000"	.083"	W - D.O.M.	2.834"	--	--	DT24-30-42
3.000"	.095"	W	2.810"	--	24-30-12-7400	24-30-12-10000
3.000"	.120"	S	2.760"	--	--	24-32-142-10000
3.000"	.134"	W	2.732"	--	24-30-72-7400	24-30-72-10000
3.500"	.065"	W	3.370"	--	28-30-42-7400	28-30-42-10000
3.500"	.065"	W - D.O.M.	3.370"	--	--	DT28-30-42
3.500"	.083"	W	3.334"	--	28-30-62-7400	28-30-62-10000
3.500"	.083"	W - D.O.M.	3.334"	--	--	DT28-30-62
3.500"	.095"	W	3.310"	--	28-30-22-7400	28-30-22-10000
3.500"	.095"	W - D.O.M.	3.310"	--	--	DT28-30-22
3.500"	.134"	W	3.232"	--	28-30-92-7400	28-30-92-10000
3.500"	.134"	W - D.O.M.	3.232"	--	--	DT28-30-92
3.500"	.156"	W	3.188"	--	28-30-52-7400	28-30-52-10000
3.500"	.156"	W - D.O.M.	3.188"	--	--	DT28-30-52
3.550"	.207"	W - D.O.M.	3.136"	28-30-122-6800	--	28-30-122-10000
4.000"	.065"	W - D.O.M.	3.870"	--	DT143T	--
4.000"	.083"	S	3.834"	32-38-12-1640M(1)	--	--
4.000"	.083"	W	3.834"	--	32-30-22-7400	32-30-22-10000
4.000"	.083"	W - D.O.M.	3.834"	--	--	DT32-30-22
4.000"	.095"	W	3.810"	--	32-30-12-7400	32-30-12-10000
4.000"	.120"	W	3.760"	--	32-30-42-7400	--
4.000"	.134"	W	3.732"	--	32-30-52-7400	32-30-52-10000
4.000"	.134"	W - D.O.M.	3.732"	--	32-30-92-7300	32-30-92-10000(2)
4.095"	.180"	W - D.O.M.	3.735"	--	32-30-72-7300	32-30-72-10000(3)
4.213"	.138"	W - D.O.M.	3.937"	--	100-30-3-7300	100-30-3-10000(4)
4.331"	.197"	W - D.O.M.	3.937"	--	100-30-5-7300	100-30-5-10000(4)
4.500"	.134"	W - D.O.M.	4.232"	--	36-30-62-7300	36-30-62-10000(5)
4.500"	.259"	W - D.O.M.	3.982"	--	36-30-22-7300	36-30-22-10000
4.540"	.083"	S	4.374	5002511-1679M(6)	--	--
4.590"	.180"	W - D.O.M.	4.230"	--	36-30-102-7300	36-30-102-10000
4.724"	.197"	W - D.O.M.	4.330"	--	110-30-5-7300	110-30-5-10000(4)
4.961"	.118"	W - D.O.M.	4.725"	--	120-30-3-7300	120-30-3-10000(4)
5.059"	.167"	W - D.O.M.	4.725"	--	120-30-4-7300	120-30-4-10000(4)
5.118"	.197"	W - D.O.M.	4.725"	--	120-30-5-7300	120-30-5-10000(4)
5.197"	.236"	W - D.O.M.	4.725"	--	120-30-6-7300	120-30-6-10000(4)

(1) Aluminum Tube; 64 18/32" Length

(2) Replaces 4.062" - .165" wall tube.

(3) Use in the place of 4.000" - .134" tube when heavy duty tubing is required.

(4) Metric tubing used on Spicer Life™ driveshafts.

(5) Use in the place of 4.562" - .165" tube when heavy duty tubing is required.

(6) Aluminum Tube; 66 3/32" Length

D.O.M. (Drawn Over Mandrel) tubing is not seamless.

Dana Corporation
Heavy Vehicle Technologies and Systems Service
PO Box 321
Toledo, Ohio 43697-0321
1-800-SAY-DANA (729-3262)
www.spicerparts.com

J3203-1-HVTSS
10/06 Printed in U.S.A.

Copyright Dana Corporation, 2006.
All rights reserved.