

SPICER®



Spicer®

XFE 75W-85 Extra Fuel-Efficient Synthetic Gear Lubricant



Spicer® XFE 75W-85 Extra Fuel-Efficient Synthetic Gear Lubricant

1.9% fuel savings. Unparalleled performance. Our most fuel-efficient gear lubricant to date. Spicer® XFE 75W-85 delivers fuel savings that makes a noticeable impact on your bottom line. Engineered to meet the specifications of linehaul, vocational heavy-duty axles, and light-duty axles. Experience long gear life and premium operating performance, even in extreme temperatures. You can enjoy a 1.9% fuel savings when compared to a traditional FE-75W-90 oil, and extend the warranty on your Spicer heavy-duty or medium-duty carriers.



Spicer® XFE 75W-85 Extra Fuel-Efficient Synthetic Gear Lubricant

Advantages and Benefits:

- Improved fuel efficiency: Additional 1.9%* fuel savings when compared to traditional FE 75W-90 oil
- Extended drain interval; up to 500,000 miles
- Outstanding gear and bearing protection
- Extreme hot and cold temperature performance

Specifications and OEM Approvals:

Spicer® XFE 75W-85 extra fuel-efficient synthetic gear lubricant is approved to meet the most stringent industry specifications, as established by Dana:

- API Category GL-5
- API Category MT-1
- SAE J2360
- Dana SHAES 256 REV E**
- Dana SHAES 429**
- Meritor O76-S
- Mack GO J

Get an Extended Warranty When You Purchase Spicer® Gear Lube!

Purchase a new heavy-duty or medium-duty Spicer service carrier for your linehaul vehicle and fill it with Spicer® XFE 75W-85 extra fuel-efficient synthetic gear lubricant. When doing so, you can extend your 2-year unlimited warranty by an additional 12 months for a total of 3 years. For more details on how to register for this extended warranty, visit our website at SpicerParts.com/Carriers.

Characteristics:

Properties	Unit	Typical Value	Method
SAE Viscosity Grade		75W85	SAE J306
Density at 15.6 °C	g/ml (lbs/gal. US)	0.864 (7.21)	ASTM D 1298
Viscosity at 100° C	mm ² /s	168	ASTM D 2270
at 40° C	mm ² /s	12.9	ASTM D 445
at -40° C	mPas	77.2	ASTM D 445
Flash Point	°C	32,000	ASTM D 2983
Pour Point	°C	210	ASTM D 92
Shear Stability (200 hrs)	% viscosity loss (shear)	-57	ASTM D 97
		1.2	CEC L-45-99-A (KRL)

NOTE: Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally.



Spicer® XFE 75W-85 extra fuel-efficient synthetic gear lubricant delivers better operating performance and a 1.9%* fuel savings when compared to a traditional FE 75W-90 oil.

**1.9%
FUEL
SAVINGS***

* Fuel savings based on initial results of applications tested. Results may vary.

Spicer Part #	Size
XFE75W85-P	5-gallon pail

Calculate the savings at SpicerParts.com/FuelSavings.
For additional information on Spicer products visit SpicerParts.com.
For our e-catalog and parts locator, visit DanaAftermarket.com.

* Fuel savings based on initial results of applications tested. Results may vary.

** Interim

Please refer to safety data sheet for handling details. Subject to appropriate storage in closed original containers under the usual storage and temperature conditions. Spicer XFE 75W-85 extra fuel-efficient synthetic gear lubricant is stable in storage for 3 years.

SpicerParts.com/Lubricants

Dana Aftermarket Group

PO Box 1000 Maumee, Ohio 43537

Warehouse Distributors: 1.800.621.8084

OE Dealers: 1.877.777.5360

Follow SpicerParts [f](#) [t](#) [c](#) [m](#) [in](#)

© 2020 Dana Limited. All rights reserved. SPR-XFE85-SS-62020

SPICER®

